



D-Foam

Always check and read carefully the Material Safety Data Sheet before use.

USES: D-Foam-552 is a special blend of anti-foam additives that will help eliminate foaming problems in your parts washers and other equipment where it might be necessary. 552 contains dimethyl methylhydroxy propyl ethoxylated propoxylated siloxane, polydimethyl siloxane and water. 552 is completely biodegradable.

FIRST AID:

EYES: Immediately flush with water while forcibly holding eyelids open for optimum irrigation for 15 minutes. Get medical attention immediately.

SKIN: Wash thoroughly with water.

INTERNAL: Induce vomiting.

CAUTION: Use in a well ventilated area. Can be an irritant to skin and eyes. If swallowed D-Foam-552 may be harmful.

DIRECTIONS:

Depending on the amount of foaming use anywhere from 2-4 ounces at a time as needed to reduce the foam levels. Use more if the level will not go down as far as you want.

VOC Content: < 1 gram per liter

HMIS:

Health = 1

Flammability = 0

Reactivity = 0

For Industrial Use Only

Keep Away From Children

" Proud to be American owned & operated"

FOR MEDICAL EMERGENCY CONTACT: ROCKY MOUNTAIN POISON CENTER: 303-739-1110
FOR EMERGENCY SPILLS CONTACT: CHEMTREC: 1-800-424-9300, OUTSIDE U.S.: 703-527-3887

1 Gallon